

Product Carbon Footprint Dashboard

powered by carboncalcpcf.com

Total PCF for sjjkxqddzs

27.54 kg CO2e

Key Carbon Metrics

Total Product Footprint

27.54 kg CO₂e

Carbon Intensity

27.54 kg CO₂e/unit

Top Material Hotspot

Aluminum Casing

Primary Emission Scope

Scope 3 (91.8%)

Emission Breakdown & Hotspots

Material Optimization: Explore lower-carbon alternatives like recycled aluminum, or design modifications to reduce the quantity of high-impact materials used.

Renewable Energy Procurement: Increase the share of renewable energy in manufacturing operations beyond the current 40% (hqwedlilmj) and engage suppliers in similar transitions.

Energy Efficiency in Use: Implement product design enhancements to reduce energy consumption during the product's 5-year lifespan (ngeswzsfvg) in the use phase.

Supply Chain Engagement: Work with upstream suppliers to acquire specific primary emission data and encourage their decarbonization efforts.

Circular Economy Initiatives: Enhance existing take-back programs (iepfurqujm) and explore closed-loop recycling to maximize material recovery and reduce virgin material demand.

Product: sjjkxqddzs | Quantity: 1.0 unit | System Boundary: factory_gate (cradle-to-grave analysis for full Scope 3 coverage) | Production Country: China |
Standard: GHG Protocol

Generated Date: May 31, 2026